

# Jason Bottom Rolling Sliding Door Gear

## FOR CUPBOARD AND WARDROBE DOORS

### APPLICATION

Bottom rolling system for cupboard, wardrobe or similar domestic doors, single or multiple track runs.

### RANGE

- Maximum door weight 25kg (50lb).
- Maximum door height 1.5m (5ft).
- Maximum door width 1m (3ft 3ins).

### DOOR CONSTRUCTION

Minimum door thickness 12mm solid. Width one third height minimum, handle three fifths from bottom for best results.

### FIXING

Top channel soffit fixed, floor track recessed or surface mounted. Side fixing rollers suit 12mm doors minimum. Close clearances need to be maintained to ensure correct operation. Position rollers close to edge of door.

### BOTTOM ROLLERS

Side fixing. Steel casing, zinc plated, nylon wheels, ground steel axles.

### BOTTOM TRACK

60-2 Aluminium, drilled and c/sk for woodscrews. Lengths 1.2m and 1.8m.

### TOP GUIDE

Nylon edge fixing.

### TOP GUIDE CHANNEL

40-2 Aluminium, drilled and c/sk for woodscrews. Lengths 1.2m and 1.8m.

### DOOR STOP

97-728 Nylon.

### FINGER PULL

95-611 White plastic, size 32mm diameter, 8mm deep.

### STANDARD TRACKSETS

**SET 4 J** – For two doors within 1.2m opening.

**SET 6 J** – For two doors within 1.8m opening.

Contents per set: 2 lengths of bottom track, 2 lengths of top channel, 4 bottom rollers, 4 nylon top guides, finger pulls, door stop and all screws.

### TWO DOOR COMPONENT PACK 2 J

Comprising all necessary bottom rollers, top guides, door stop finger pulls and screws for two doors.

### TOP CHANNEL AND BOTTOM TRACK

Available in 1.2m and 1.8m lengths.

